



“Armaments for the Army Transformation”

NDIA Conference & Exhibition
Parsippany Hilton, Parsippany NJ

Advanced Penetrator Materials

Dr. Lee Magness*

Lethal Mechanisms Branch
Weapons Materials Division

Phone: 410-278-6022

E-mail: magness@arl.army.mil

20 June 2001

Report Documentation Page

Report Date 20JUN2001	Report Type N/A	Dates Covered (from... to) -
Title and Subtitle Advanced Penetrator Materials	Contract Number	
	Grant Number	
	Program Element Number	
Author(s) Magness, Lee	Project Number	
	Task Number	
	Work Unit Number	
Performing Organization Name(s) and Address(es) Lethal Mechanisms Branch Weapons Materials Division Army Research Laboratory	Performing Organization Report Number	
Sponsoring/Monitoring Agency Name(s) and Address(es) NDIA (National Defense Industrial Association 2111 Wilson Blvd., Ste. 400 Arlington, VA 22201-3061	Sponsor/Monitor's Acronym(s)	
	Sponsor/Monitor's Report Number(s)	
Distribution/Availability Statement Approved for public release, distribution unlimited		
Supplementary Notes Proceedings from Armaments for the Army Transformation Conference, 18-20 June 2001 sponsored by NDIA		
Abstract		
Subject Terms		
Report Classification unclassified	Classification of this page unclassified	
Classification of Abstract unclassified	Limitation of Abstract UU	
Number of Pages 23		




OUTLINE



- Background: Relationships between Properties and Performance of High-Density Materials
 - the adiabatic shear failure of DU
 - general approaches to alloy development
- Uranium (U-V-X) Alloys
- Alternative Matrix (adiabatic shearing) Tungsten Composites
- Amorphous and Nanocrystalline Alloys
- Severe Deformation Processed WHAs
- Jacketed Penetrators
- Conclusions




Properties vs. Performance Relationships/Requirements



- Engineering properties: strength and toughness.
 - Allow more efficient sabots/projectiles.
 - Resist complex armors.
 - Soft-launched projectiles expand options.


- High-rate, high pressure, deformation.
 - Controls efficiency during deep penetration.

At the present time, Depleted Uranium alloys provide the best overall combination of structural and high-rate properties.






Pressure & Strain Rate Distributions During Deep Penetration



2DC Block 1
W alloy rod into semi-infinite RHA at 1300 m/s
HFIFFU 08/06/98 09:01:34 CTH 466 Time= 4.00752×10^{-5}




2DC Block 1
W alloy rod into semi-infinite RHA at 1300 m/s
HFIFFU 08/06/98 09:01:34 CTH 466 Time= 4.00752×10^{-5}


Strain-hardening and thermal-softening mechanisms compete during the high rate (adiabatic) deformation.




Flow/Failure of High-Density Penetrator Materials



PURE W



CONVENTIONAL
WHA



DU-3/4Ti


DU failure by adiabatic shear. This reduces the size of penetrator head, burrows narrower & deeper cavity.




Flow and Failure of High Density Penetrator Materials




TUNGSTEN HEAVY ALLOY



- WIDER CHANNEL
- MUSHROOM NOSE
- LESS DEPTH




W-Ni-Fe



U-3/4 Ti ALLOY



- REMAINS SHARP
- NARROW CHANNEL
- DEEPER CAVITY






U-8Mo ALLOY



Dynamic (SHB) Compression Tests

(strain to adiabatic shear failure)



**U-3/4Ti specimen
cleaved by shear band**


Dynamic compression experiments provide a means for assessing material failure behavior at high loading rates.



Comparison of RHA Steel Perforation Capabilities



1/4-scale tests, 65g L/D=15 rods vs. 76.2mm RHA



Deep Penetration performance is a function of alloy density & strain to shear failure.




Material Options



- **DU alloys:** Enhance susceptibility to shear failure, while retaining/improving engineering properties.
- **Non-DU materials:** change flow/failure behavior
 - Use alternative matrices, selection based on mechanical and thermal properties that promote high-rate (adiabatic) plastic instability and localization
 - Matrix alloys w/high strength, low work hardening, low strain rate sensitivity, rapid thermal softening
 - Amorphous & nanocrystalline materials as a candidate matrix alloy or entire composite (nano W phase)
 - exhibit localized shear failure in dynamic and quasi-static tests
 - Anisotropic flow/failure of W crystals
- **Jacketed Penetrators:** Systems approach, with materials issues



CURRENT ANTI-ARMOR MATERIALS DEVELOPMENT PROGRAMS



Center of
Excellence
Programs

TPA

SBIR/STTR
Contracts

International
Agreements

Congressional
Interest
Program

Industry

ARO
University
Programs

DARPA

Customer

Other
Government
Agencies





Uranium-Vanadium Alloys



Composition	Density	Hardness	Ult. Tensile Strength
	(g/cc)	HRC	(Ksi/Mpa)
U-V (1-4.5%)	16.7–18.5	36-54	To 310/2140
U-V-X(ternary)	16-18.5	36-55	To 320/2200
U-3/4Ti	18.6	38-49	To 250/1720

U-2.1% V,
banded
martensite
(from Staker)




U-.75% Ti,
acicular
martensite
(from Staker)


- U-V alloys have the potential to maintain penetration capability while reducing penetrator density and mass.



Tungsten Composites with Adiabatic Shearing Matrix Alloys



Residual Ti6Al4V Penetrator





**Residual W-Ti alloy
Composite Penetrator**


- Replace conventional Ni-Fe matrix alloy with one more prone to adiabatic shear failure, to enhance plastic instability.



Dynamic Compression Tests of Hafnium and Hafnium Alloy



Unalloyed Hf




HB6, Hf10Ti10Ta

- Hafnium alloy HB6 demonstrated the preferred failure behavior in dynamic compression tests.



Perforation of Steel



Performance of W composite with hafnium alloy matrix significantly better than conventional (Ni-Fe)-matrix WHAs, but still short of DU.





W Composites with Bulk



Amorphous Metal (BAM) Matrices

- Amorphous alloys lack long-range structure of crystalline solids.





Crystalline

Amorphous

- Unique mechanical properties: high elastic limit (2-3% strain, 1.6GPa Y.S., no work-hardening).
- Recent development of complex, multi-component bulk metallic glass alloys make 1 to 5 cm thick sections possible (low quench rates)

Typical Mechanical Behavior: no strain hardening in quasi-static S-e curve, serrated plastic flow (shear banding)



Angled ($\sim 45^\circ$) shear band failure


“Deformation Mechanisms of the ZrTiNiCuBe Metallic Glass”,
Wright, Saha, & Nix



W Composites with Bulk Amorphous Metal (BAM) Matrices




- ARO-funded CalTech development of W-composite using Z-Ti-Cu-Ni-Be bulk castable amorphous alloy



Tungsten wire/
amorphous alloy
composite.

80% wire
reinforced.



Sub-scale ballistic tests suggest DU-like improvement in penetration performance. From ARO grant to CalTech (W. Johnson)






Nanocrystalline Materials



- Like amorphous metals, nanocrystalline (<100 nm GS) metals exhibit little or no work-hardening or bulk plasticity in quasi-static tests
- Shear banding behavior has been observed in materials with GS >250 nm



Tests by Dexin Jia, of Johns Hopkins U., aver.GS 268 nm




Ballistic Tests of Nanocrystalline W-Composite



Penetrator Type	Material	Density	Limit Velocity
		(kg/m ³)	(m/s)
Depleted Uranium	U-3/4 Ti, Rc 40	18600	1260
Conventional WHA	90W-9Ni-1Co	17100	1390
Nano W-Composite	W-Cu-Ni-Al	15200	1347
W-Composite w/Hf matrix	80W-20 HB3	17000	1350

- Performance of nanocomposite surpassed that of conventional WHA or best adiabatic-shearing matrix, despite lower density
- DU vs. WHA performances narrowed, but DU is still superior




Nano W-Composite Penetrator Erosion Products Lining Penetrator Tunnel (15X)



SEVERE PLASTIC DEFORMATION PROCESSING


Equi-Channel Angular Pressing (ECAP)

- New Mechanical Working Technique
- Developed in FSU
- Path to improved mechanical properties or alternative path to grain size refinement (nano)



Key Features

- Cross section in equals cross section out.
- Pure shear deformation
- Imparts cold work (>99%) with or w/o microstructural changes (reversible).
- Multiple passes increase deformation, refine grain size




5056 Aluminum Alloy
ECAE, >2x strength

<u>#Of Passes</u>	<u>Equiv. Reduction</u>
1	69%
2	90
4	99
8	99.99




TEM STRUCTURE AND MICRODIFFRACTION PATTERN 8 PASSES, ROUTE C



Cross Section

1 μm



Die Angle of 110°
Route C, 4 Passes

- Ultra Fine Grained (UFG) Structure
- Mean Grain Size Approximately $1 \mu\text{m}$, many grains 0.3 to $0.5 \mu\text{m}$



Material Bonding for Jacketed Penetrators



Goals: Fracture Resistance, Improved Stiffness, Reduced Mass




Jacket Material
Selection and Bond
Strength will be Key to
success




Candidate bonding techniques guided by ballistic experiments and simulations; FOCUS – High Strength Bonds

Thermal Spray




Explosive Cladding






Material Bonding for Jacketed Penetrators



- ✓ Metallography
- ✓ Centerline Properties
- ✓ High Strength Bond



- High Strength Bond Achieved!
 - Subscale Experiments Pending
 - Reactive & Passive Targets
- Follow-on contract in place.
 - Full Scale Processing
- Iterate based on Ballistic Results.
- Future – Consider alternate bonding.
 - Swaging
 - Co-extrusion
 - Cold Spray



Conclusions/Summary



- Certain minimum mechanical properties required for launch, for performance vs. complex armors
- Efficient flow & failure behaviors improve penetration performance against thick monolithic armor and individual armor components (e.g. basal armor behind ERA applique)
- Alloy development efforts must meet both goals